


LIFTING

Lifting points – ready for bolting



VWBG
VIP Load ring for bolting

Thread sizes
M33 – M150
1 1/2" – 5"

further thread types
and special lengths
on request.

see p.52

											Thread sizes M33 – M150 1 1/2" – 5" further thread types and special lengths on request. see p.52		
6t (7.5t)	8t (10t)	12t (13t)	12t (15t)	13t (16t)	14t (20t)	16t (22t)	16t (25t)	31.5t (40t)	35t (48t)	40t (50t)	type		
M33	M36– M39	M42– M45	M45	M48– M52	M52	M56– M62	M64– M76	M72– M76	M80– M85	M90– M150	thread size		
–	1 1/2"	1 3/4"– 1 7/8"	–	2"	–	2 1/4"– 2 1/2"	2 3/4"– 3"	3"	3 1/2"	4"– 5"	β	number of legs	
15	15	17	18	18	25	28	28	50	50	50	0°	1	
30	30	34	36	36	50	56	56	100	100	100	0°	2	
6 (7.5)	8 (10)	12 (13)	12 (15)	13 (16)	14 (20)	16 (22)	16 (25)	31.5 (40)	35 (48)	40 (50)	90°	1	
12 (15)	16 (20)	24 (26)	24 (30)	26 (32)	28 (40)	32 (44)	32 (50)	63 (80)	70 (96)	80 (100)	90°	2	
8.4 (10.5)	11.2 (14)	16.8 (18.2)	16.8 (21)	18.2 (22.4)	19.6 (28)	22.4 (30.8)	22.4 (35)	44.1 (56)	49 (67.2)	56 (70)	0-45°	2	
6 (7.5)	8 (10)	12 (13)	12 (15)	13 (16)	14 (20)	16 (22)	16 (25)	31.5 (40)	35 (48)	40 (50)	45-60°	2	
6 (7.5)	8 (10)	12 (13)	12 (15)	13 (16)	14 (20)	16 (22)	16 (25)	31.5 (40)	35 (48)	40 (50)	unsym- metrical	2	
12.6 (15.75)	16.8 (21)	25.2 (27.3)	25.2 (31.5)	27.3 (33.6)	29.4 (42)	33.6 (46.2)	33.6 (52.5)	66.15 (84)	73.5 (100.8)	84 (105)	0-45°	3+4	
9 (11.2)	12 (15)	18 (19.5)	18 (22.5)	19.5 (24)	21 (30)	24 (33)	24 (37.5)	47.25 (60)	52.5 (72)	60 (75)	45-60°	3+4	
6 (7.5)	8 (10)	12 (13)	12 (15)	13 (16)	14 (20)	16 (22)	16 (25)	31.5 (40)	35 (48)	40 (50)	unsym- metrical	3+4	

Higher WLL () due to optimised attachment
or usage (see product page).