



WORKING LOAD LIMIT

Maximum transport weight "G" in [t] with different lifting points

WLL 0.63 t – 8 t see p.136		PowerPoint / pivoting 360°			not pivoting			
								
		WPP-S / WPP-B / WPP-VIP			WPPH-S /H-B /H-VIP			
		S-Star / B-Ring connect. / VIP chain connect.			S-Star / B-Ring connect. / VIP chain connect.			
type		0.63 t	1.5 t	2.5 t	4 t	5 t	8 t	
weld seam		a 4 	a 5 	HY 3 + a 5 	HY 3 + a 6 	HY 3 + a 8 	HY 3 + a 10 	
	number of legs	β						
	β							
	1	0°	0.63	1.5	2.5	4	6.7	10
	2	0°	1.26	3	5	8	13.4	20
	1	90°	0.63	1.5	2.5	4	5	8
	2	90°	1.26	3	5	8	10	16
	2	0-45°	0.88	2.1	3.5	5.6	7	11.2
	2	45-60°	0.63	1.5	2.5	4	5	8
	2	unsymmetrical	0.63	1.5	2.5	4	5	8
	3+4	0-45°	1.32	3.15	5.25	8.4	10.5	16.8
	3+4	45-60°	0.95	2.25	3.75	6	7.5	12
	3+4	unsymmetrical	0.63	1.5	2.5	4	5	8

Higher WL () due to optimised attachment or usage (see product page).